

GATE OPERATOR FOR CLASS I INSTALLATIONS



Pedestal or post mounting minimizes the pad required, while under-the-housing gate arm allows a completely weather-resistant system.

TWIST'R PLUS

Slide Gate Operator - Model RSX4000

MAX Gate Length: 16 FT.

MAX Gate Weight: 300 lbs.

Features

- CGA2K™ Technology
- UL325 & 991 Listed
- 1/2 HP Motor
- Durable, Architecturally Designed Weather-Resistant Cover
- Built-In Maximum Run Timer for Added Safety
- Built-In Adjustable Auto-Close Timer
- Built-In Master/Slave Capability
- Easy Conversion Right-Hand/Left-Hand Drive
- Radial-Swing Limit Switches for Easy Adjustment

- Poly-Vee Belt Final Drive with Adjustable Torque Output
- Pre-wired 9931 Receiver
- Entry System Capable

Options

- Radio Controls
- Standby Power Supply (battery backup)
- Photobeams
- Electric Edges
- Mounting Pedestal
- Traffic Control Devices



CGA2K™ Technology

Standard On Every Allstar Gate Operator

Features

- UL325 & 991 Listed
- Selectable Control by Additional Operator (Master/Slave)
- Adjustable Auto-Close Timer (off, 2-60 seconds)
- Self-Adjusting Maximum Run timer

- Separate Inputs for Access Control Devices and Entrapment Protection devices

Toll Free: 877-441-9300
Toll Free: 800-421-1587
Toll Free FAX: 877-523-2963
e-mail: info@allstarcorp.com
web site: www.allstarcorp.com

